

SAFETY DATA SHEET

Issuing Date No data available

Revision Date 20-Nov-2015

Revision Number 3



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is © 2014 UL LLC. All rights reserved.

Product identifier

Product Name Isopropyl Alcohol 70 Percent Large Qty

Other means of identification

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Antibacterial Used for Personal Care

Uses advised against No information available

Details of the supplier of the safety data sheet

Supplier Name PL Developments

Supplier Address 1874 Hwy 72 West
Clinton, SC 29325

US

Supplier Phone Number Phone:864-833-0178

Supplier Email KGASTON@PLDEVELOPMENTS.COM

Emergency telephone number

Company Emergency Phone Number 864-833-0178

SDS# 173 ITEM# 890890

Classification


This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200).

Serious eye damage/eye irritation	Category 2
Specific target organ toxicity (single exposure)	Category 3
Flammable liquids	Category 2



GHS Label elements, including precautionary statements

Emergency Overview

Signal word	Danger
Hazard Statements Causes serious eye irritation May cause drowsiness or dizziness Highly flammable liquid and vapor	
	
Appearance Clear, colorless	Physical state Liquid Odor Alcohol

Precautionary Statements - Prevention

- Wash face, hands and any exposed skin thoroughly after handling
- Wear protective gloves/protective clothing/eye protection/face protection
- Avoid breathing dust/fume/gas/mist/vapors/spray
- Use only outdoors or in a well-ventilated area
- Keep away from heat/sparks/open flames/hot surfaces. - No smoking
- Keep container tightly closed
- Ground/bond container and receiving equipment
- Use explosion-proof electrical/ ventilating/ lighting/ equipment
- Use only non-sparking tools
- Take precautionary measures against static discharge
- Keep cool
- Wear eye/face protection

Precautionary Statements - Response

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 If eye irritation persists: Get medical advice/attention

Skin

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
 Call a POISON CENTER or doctor/physician if you feel unwell

Fire

In case of fire: Use CO2, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store in a well-ventilated place. Keep container tightly closed
 Store locked up



Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Unknown Toxicity

0 % of the mixture consists of ingredient(s) of unknown toxicity

Other information

May be harmful if swallowed

PROLONGED OR REPEATED CONTACT MAY DRY SKIN AND CAUSE IRRITATION

Interactions with Other Chemicals

No information available.



Chemical name	CAS No	Weight-%	Trade Secret
Isopropyl alcohol	67-63-0	60 - 100	*

*The exact percentage (concentration) of composition has been withheld as a trade secret



First aid measures

General Advice

Show this safety data sheet to the doctor in attendance.

Eye contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. Get medical attention if irritation develops and persists.

Skin contact

Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.

Inhalation

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, (trained personnel should) give oxygen.

Ingestion

Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Call a physician.

Self-protection of the first aider

Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid contact with skin, eyes or clothing. Wear personal protective clothing (see section 8).

Most important symptoms and effects, both acute and delayed

Most Important Symptoms and Effects

Burning sensation. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Indication of any immediate medical attention and special treatment needed



Notes to Physician

Effects of exposure (inhalation, ingestion or skin contact) to substance may be delayed.

Suitable Extinguishing MediaDry chemical. Carbon dioxide (CO₂). Water spray. Alcohol resistant foam.**Unsuitable extinguishing media**

CAUTION: All these products have a very low flash point: Use of water spray when fighting fire may be inefficient. Do not use dry chemical extinguishers to control fires involving nitromethane or nitroethane. Do not use straight streams.

Specific hazards arising from the chemical

Vapors can form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapor explosion hazard indoors, outdoors or in sewers. Runoff to sewer may create fire or explosion hazard.

Uniform Fire Code

Irritant: Liquid

Explosion Data**Sensitivity to Mechanical Impact** None.**Sensitivity to Static Discharge** Yes.**Protective equipment and precautions for firefighters**

Move containers from fire area if you can do it without risk. Damaged cylinders should be handled only by specialists.

Personal precautions, protective equipment and emergency procedures**Personal precautions**

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). All equipment used when handling the product must be grounded. Do not touch or walk through spilled material. Stop leak if you can do it without risk.

Other Information

Water spray may reduce vapor; but may not prevent ignition in closed spaces.

Environmental precautions**Environmental precautions**

Prevent entry into waterways, sewers, basements or confined areas.

Methods and material for containment and cleaning up**Methods for containment**

A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers.

Methods for cleaning up

Use clean non-sparking tools to collect absorbed material. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.



Precautions for safe handling

Handling

Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Use personal protection equipment. Avoid contact with skin and eyes. Avoid breathing vapors or mists. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions.

Conditions for safe storage, including any incompatibilities

Storage

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations.

Incompatible Products

Strong oxidizing agents. Acids. Chlorinated compounds.

Control parameters

Exposure Guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Isopropyl alcohol 67-63-0	STEL: 400 ppm TWA: 200 ppm	TWA: 400 ppm TWA: 980 mg/m ³ (vacated) TWA: 400 ppm (vacated) TWA: 980 mg/m ³ (vacated) STEL: 500 ppm (vacated) STEL: 1225 mg/m ³	IDLH: 2000 ppm 10% LEL TWA: 980 mg/m ³ TWA: 400 ppm STEL: 500 ppm STEL: 1225 mg/m ³

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits NIOSH IDLH Immediately Dangerous to Life or Health

Other Exposure Guidelines

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992)

Appropriate engineering controls

Engineering Measures

Showers
Eyewash stations
Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/face protection

Tight sealing safety goggles.

Skin and body protection

Wear protective gloves and protective clothing. Long sleeved clothing. Chemical resistant apron. Impervious gloves. Antistatic boots.



Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product.

Physical and Chemical Properties

Physical state	Liquid	Odor	Alcohol
Appearance	Clear, colorless	Odor Threshold	No information available
Color	No information available		

<u>Property</u>	<u>Values</u>	<u>Remarks</u>	<u>Method</u>
pH	7	None known	
Melting / freezing point	No data available	None known	
Boiling point / boiling range	82 °C / 180 °F	None known	
Flash Point	12 C / 54 F	None known	
Evaporation Rate	No data available	None known	
Flammability (solid, gas)	No data available	None known	
Flammability Limit in Air			
Upper flammability limit	No data available		
Lower flammability limit	No data available		
Vapor pressure	No data available	None known	
Vapor density	No data available	None known	
Specific Gravity	0.87	None known	
Water Solubility	Soluble in water	None known	
Solubility in other solvents	No data available	None known	
Partition coefficient: n-octanol/water	0.05	None known	
Autoignition temperature	No data available	None known	
Decomposition temperature	No data available	None known	
Kinematic viscosity	No data available	None known	
Dynamic viscosity	No data available	None known	
Explosive properties	No data available		
Oxidizing properties	No data available		

Other Information

Softening Point	No data available
VOC Content (%)	No data available
Particle Size	No data available
Particle Size Distribution	



Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Strong oxidizing agents. Acids. Chlorinated compounds.

Hazardous Decomposition Products

Carbon oxides.

Information on likely routes of exposure**Product Information**

Inhalation	Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract. May cause drowsiness or dizziness.
Eye contact	Specific test data for the substance or mixture is not available. Causes serious eye irritation. (based on components). May cause redness, itching, and pain.
Skin contact	Specific test data for the substance or mixture is not available. May cause irritation. Prolonged contact may cause redness and irritation.
Ingestion	Specific test data for the substance or mixture is not available. Ingestion may cause irritation to mucous membranes. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Isopropyl alcohol 67-63-0	= 1870 mg/kg (Rat)	= 4059 mg/kg (Rabbit)	= 72600 mg/m ³ (Rat) 4 h

Information on toxicological effects

Symptoms May cause redness and tearing of the eyes. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.

Mutagenic Effects No information available.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Isopropyl alcohol		Group 3		X



67-63-0				
---------	--	--	--	--

IARC (International Agency for Research on Cancer)
 Group 3 - Not Classifiable as to Carcinogenicity in Humans
OSHA (Occupational Safety and Health Administration of the US Department of Labor)
 X - Present

Reproductive toxicity No information available.
STOT - single exposure No information available.
STOT - repeated exposure No information available.
Chronic Toxicity No known effect based on information supplied.
Target Organ Effects Eyes.
Aspiration Hazard No information available.

Numerical measures of toxicity Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)
 2,671.00 mg/kg
ATEmix (dermal)
 5,799.00 mg/kg (ATE)
ATEmix (inhalation-dust/mist)
 103.70 mg/l



Ecotoxicity

The environmental impact of this product has not been fully investigated.

Chemical name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Isopropyl alcohol 67-63-0	96h EC50: > 1000 mg/L (Desmodesmus subspicatus) 72h EC50: > 1000 mg/L (Desmodesmus subspicatus)	96h LC50: > 1400000 µg/L (Lepomis macrochirus) 96h LC50: = 11130 mg/L (Pimephales promelas) 96h LC50: = 9640 mg/L (Pimephales promelas)		48h EC50: = 13299 mg/L

Persistence and Degradability

No information available.

Bioaccumulation

Chemical name	Log Pow
Isopropyl alcohol 67-63-0	0.05

Other adverse effects

No information available.



Waste treatment methods

Disposal methods This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).

Contaminated Packaging Dispose of contents/containers in accordance with local regulations.

US EPA Waste Number D001

California Hazardous Waste Codes 311

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical name	California Hazardous Waste
Isopropyl alcohol 67-63-0	Toxic Ignitable

DOT

Proper Shipping Name CONSUMER COMMODITY
Hazard Class ORM-D
Description CONSUMER COMMODITY, ORM-D
Emergency Response Guide Number 129

TDG

UN-No. UN1219
Proper Shipping Name ISOPROPANOL
Hazard Class 3
Packing Group II
Description UN1219, ISOPROPANOL, 3, II

MEX

UN-No. UN1219
Proper Shipping Name ISOPROPANOL
Hazard Class 3
Packing Group II
Description UN1219, ISOPROPANOL, 3, II

ICAO

UN-No. UN1219
Proper Shipping Name ISOPROPANOL
Hazard Class 3
Packing Group II
Description UN1219, ISOPROPANOL, 3, II

IATA

UN-No. UN1219
Proper Shipping Name ISOPROPANOL
Hazard Class 3
Packing Group II
ERG Code 3L



Description UN1219, ISOPROPANOL, 3, II

IMDG/IMO

UN-No. UN1219
Proper Shipping Name ISOPROPANOL
Hazard Class 3
Packing Group II
EmS-No. F-E, S-D
Description UN1219, ISOPROPANOL, 3, II, (12°C C.C.)

RID

UN-No. UN1219
Proper Shipping Name ISOPROPANOL
Hazard Class 3
Packing Group II
Classification code F1
Description UN1219, ISOPROPANOL, 3, II

ADR

UN-No. UN1219
Proper Shipping Name ISOPROPANOL
Hazard Class 3
Packing Group II
Classification code F1
Tunnel restriction code D/E
Description UN1219, ISOPROPANOL, 3, II

ADN

UN-No. UN1219
Proper Shipping Name ISOPROPANOL
Hazard Class 3
Packing Group II
Classification code F1
Special Provisions 601
Description UN1219, ISOPROPANOL, 3, II
Hazard Labels 3
Limited Quantity 1 L
Ventilation VE01

International Inventories

TSCA Complies
DSL All components are listed either on the DSL or NDSL.
IECSC -

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	CAS No	Weight-%	SARA 313 - Threshold Values %
Isopropyl alcohol - 67-63-0	67-63-0	60 - 100	1.0

SARA 311/312 Hazard Categories



Acute Health Hazard	Yes
Chronic Health Hazard	No
Fire Hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Isopropyl alcohol 67-63-0	X	X	X	X	

International Regulations

Mexico

National occupational exposure limits

Component	Carcinogen Status	Exposure Limits
Isopropyl alcohol 67-63-0 (60 - 100)		Mexico: TWA 400 ppm Mexico: TWA 980 mg/m ³ Mexico: STEL 500 ppm Mexico: STEL 1225 mg/m ³

Mexico - Occupational Exposure Limits - Carcinogens

Canada

WHMIS Hazard Class

Not determined



NFPA	Health Hazards 2	Flammability 3	Instability 0	Physical and Chemical Hazards - Personal Protection X
HMIS	Health Hazards 2	Flammability 3	Physical Hazard 0	

Prepared By Product Stewardship
23 British American Blvd.
Latham, NY 12110
1-800-572-6501

Revision Date 20-Nov-2015

Revision Note No information available

Disclaimer



The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet