Material Safety Data Sheet May be used to comply with OSHA's Hazard Communication Standard 29 CFR 1910.1200. Standard must be

consulted for specific requirement

U.S. Department of Labor

Occupation Safety and Health Administration

(Non-Mandatory Form)

Form Approved

OMB No. 1218-0072

OMB No. 1218-007	-		
Note: Blank spaces are not permitted. If any item is not applicable, or no			
information is available, the space must be marked to indicate that.			
Emergency Telephon	e Number		
800-644-6457			
Telephone Number For Information			
800-644-6457			
Date Prepared			
March 2004			
Signature of Preparer (optional)			
	ACGIH TI V	Other Limite	% (ontions
OSHA PEL	ACCIT TEV	Recommended	% (optional

			•••••••••

Specific Gravity (H2O = 1)		
Specific Gravity (H2O = 1)		0.875
50000000000000000000000000000000000000	H2O = 1)		0.875
Specific Gravity (H2O = 1)		1-200 A COLOR
Melting Point	504500 (dino 10 4 € 0)		0.875 N/A
Melting Point Evaporation Rate			N/A
Melting Point			1-200 AUGUS
Melting Point Evaporation Rate			N/A
Melting Point Evaporation Rate			N/A
Melting Point Evaporation Rate			N/A
Melting Point Evaporation Rate			N/A
Melting Point Evaporation Rate (Butyl Acetate = 1		I EI	N/A 0.01
Melting Point Evaporation Rate		LEL 19	N/A 0.01
Melting Point Evaporation Rate (Butyl Acetate = 1		LEL 1%	N/A 0.01
Melting Point Evaporation Rate (Butyl Acetate = 1			N/A 0.01
Melting Point Evaporation Rate (Butyl Acetate = 1			N/A 0.01
Melting Point Evaporation Rate (Butyl Acetate = 1) Flammable Limits)	1%	N/A 0.01
Melting Point Evaporation Rate (Butyl Acetate = 1) Flammable Limits)		N/A 0.01
Melting Point Evaporation Rate (Butyl Acetate = 1) Flammable Limits)	1%	N/A 0.01
Melting Point Evaporation Rate (Butyl Acetate = 1) Flammable Limits)	1%	N/A 0.01
Melting Point Evaporation Rate (Butyl Acetate = 1) Flammable Limits	NTAINERS	1% WITH WATER	N/A 0.01
Melting Point Evaporation Rate (Butyl Acetate = 1) Flammable Limits	NTAINERS	1% WITH WATER RATED OXYGEN.	N/A 0.01
	Emergency Telephon 800-644-6457 Telephone Number F 800-644-6457 Date Prepared March 2004 Signature of Preparet	Emergency Telephone Number 800-644-6457 Telephone Number For Informatio 800-644-6457 Date Prepared March 2004 Signature of Preparer (optional)	information is available, the space must be marked to ind Emergency Telephone Number 800-644-6457 Telephone Number For Information 800-644-6457 Date Prepared March 2004 Signature of Preparer (optional)

Section V - R	Reactivity Data		
Stability	Unstable		Conditions to
	Stable		Avoid
Incompatibility (Materials to Avoid)	Х	
		7 <u>2</u> 72888	
			CHLORINE, CONCENTRATED OXYGEN, SODIUM OR CALCIUM
Hazardous Deco	mposition or Bypro	ducts	
FUMES, SMOR	Œ, CARBON MO	NOXIDE.	AND SULFUR OXIDES, IN THE CASE OF INCOMPLETE COMBUSTION.
Hazardous	May Occur		Conditions to
Polymerization	Will Not Occur	х	Avoid
Section VI - H	ealth Hazard Da	ta	
Route(s) of Entry		Inhalation?	
and (o) of Lifty	•	innalation?	Skin? Ingestion?
Health Hazarde //	Acute and Chronic)		
N/A	Acute and Chronic)		
21 300 CON .			
Carcinogenicity:		NTP?	IARC Monographs? OSHA Regulated?
			5 The Togulateur
Signs and Sympton			
PROLONGED O	R REPEATED S	KIN CON	TACT MAY CAUSE MILD SKIN IRRITATION.
Medical Condition	ns Generally Aggrav	ated by Ex	Sposure
N/A			
Emergency and F	irst Aid Procedure		
		WASH TI	HROUGHLY WITH SOAP AND WARM WATER. IF SPLASHED INTO EYES
FLUSH WITH	CLEAD MARED	70D 1F 1	HROUGHLY WITH SOAP AND WARM WATER. IF SPLASHED INTO EYES
Ocation NIII	CHEAR WATER I	OR 15 I	MINUTES OR UNTIL IRRITATIION SUBSIDES.
Section VII -	Precautions fo	r Safe F	landling and Use
Steps to be Taken	in Case Material is	Released of	or Spilled
RECOVER FREE	E LIQUID. AI	D ABSOR	RBENT (SAND, EARTH, SAWDUST, ETC.) TO SPILL AREA. KEEP
KEEF FROM SE	WERS OR WATE	R COURS	SES BY DIKING OR IMPOINDING ADVISE AVENUED TO THE
THOSOUT IMB	ENTEKED OK P	AY ENTE	ER SEWERS, WATER COURSES OR EXTENSIVE LAND AREAS.
The Proposition	ctriou		
FOLLOW STATE	GUIDELINES	FOR INS	STRUCTIONS ON DISPOSAL.
Precautions to be	Taken in Handling	and Storage	
KEEP CONTAIN	JERS CLOSED W	HEN NOT	TN UCE DO NOT UNITED OF THE
FT.AME OR STR	RONG OXIDANTS	HEN NOI	IN USE. DO NOT HANDLE OR STORE NEAR HEAT, SPARKS,
Other Precautions	ONG OXIDANTS	•	
	· · · · · · · · · · · · · · · · · · ·		
	G OIL MIST.		OIL-SOAKED CLOTHING AND LAUNDER BEFORE RE-USE. DISCARD
OIL-SOAKED S		SKIN TH	OROUGHLY WITH SOAP AND WATER AFTER HANDLING.
Section VIII -	Control Measu	ires	
Respiratory Protec	tion (Specify Type)		
		E SUPPL	IED-AIR RESPIRATORY PROTECTION CONFINED OR ENCLOSED
SPACES.			AIR RESPIRATORY PROTECTION CONFINED OR ENCLOSED
Ventilation	Local Exhaust	CA	PTURE FUMES, VAPOR Special > THAN 60FPM
	Mechanical(Gener		
Protective Gloves		,	Other
	DESTSMANM OF	COURS T	E MEDER TO MANAGE TO SERVICE TO S
Other Protective CI	othing or East	LOVES I.	F NEEDED TO AVOID PROLONGED SKIN.
Other Protective CI			
OSE CHEMICAL	KESISTANT A	PRON OR	OTHER CLOTHING IF NEEDED TO AVOID PROLONGED SKIN
CONTACT.			
Work/Hygienic Prac	ctices		