













# **GL503**

# Polyester | Latex | Crinkle









ANSI/ISEA 105 – CUT A1 | ABRASION 4 | PUNCTURE 3 EN388 – ABRASION 3 | CUT 2 | TEAR 4 | PUNCTURE 2 | CUT TDM-100 X EN407 – CONTACT HEAT 2

Durable latex crinkle coating on the palm and fingers offers superior contact on dry or wet surfaces by channeling liquids away // 10 gauge polyester liner is breathable and quick drying // Contact heat protection up to 482°F/250°C // Hangtag option for retail display // Packaging option for vending machines available

## **Suggested Applications**

Assembly // Bottling and Canning // Manufacturing // Recycling and Sanitation

#### Glove Breakdown

Type: Dipped Glove				
Material: Latex Crinkle				
Outer Liner: 10 Gauge Polyester				
Cuff: Polyester + Latex Elastic				

△ WARNING: Cancer and Reproductive Harm −P65Warnings.ca.gov This product contains components that may be a potential risk to allergic reactions (latex in the wrist cuff). Do not use in the event of hypersensitivity signs or a known allergy to latex.

# **Packaging**

	Inner Polybag	Outer Polybag	Case		
GL503	_	12 Pair	120 Pair		
GL503HT	_	12 Pair on Hangtags	120 Pair		
GL503VP	1 Pair Rolled	12 Pair	120 Pair		
Made in Ch	ina				

Product markings may vary // Updated as of 04.23



### **Glove Sizing**

GL503 S - 2XL | GL503HT S - 2XL | GL503VP S - XL

Small	Medium	Large	X-Large	2X-Large
7	8	9	10	11

All sizes comply with EN ISO 21420 for comfort, fit and dexterity. Only wear the correct size for your hand. Gloves that are too loose or too tight will restrict movement and will not provide the optimal level of protection.



