

Printing date 03/25/2016

Reviewed on 02/24/2015

### 1 Identification

- · Product identifier
- · Trade name: Dyno
- · Article number: 8011
- · Application of the substance / the mixture All-purpose cleaner
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

STARCO CHEMICAL

A Division of Diamond Chemical Co., Inc.

Union Avenue & Dubois Street East Rutherford, NJ 07073 Telephone: 201-935-4300

- · Information department: Product safety department
- Emergency telephone number: INFOTRAC 1-800-535-5053

### 2 Hazard(s) identification

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



**GHS05** 

- · Signal word Danger
- Hazard statements

Causes severe skin burns and eye damage.

Precautionary statements

Do not breathe dusts or mists.

Wear eye protection / face protection.

Wash thoroughly after handling.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER/doctor.

Specific treatment (see on this label).

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Wash contaminated clothing before reuse.

If eye irritation persists: Get medical advice/attention.

If swallowed: Rinse mouth. Do NOT induce vomiting.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 2)

(Contd. of page 1)

### Safety Data Sheet acc. to OSHA HCS

Printing date 03/25/2016

Reviewed on 02/24/2015

Trade name: Dyno

· Classification system:

NFPA ratings (scale 0 - 4)



Health = 3 Fire = 0Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 3 Fire = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

### 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

Components	): 	
111-76-2	2-butoxyethanol	Prop.%
13870-28-5	disodium disilicate	Prop.%
127087-87-0	Poly(oxy-1,2-ethanediyl),alpha-(4_nonylphenyl)-omega-hydoxy-, branched	Prop.%
1310-73-2	sodium hydroxide	Prop.%

### 4 First-aid measures

- Description of first aid measures
- \*General information: Immediately remove any clothing soiled by the product.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- Information for doctor:
- Most important symptoms and effects, both acute and delayed
- No further relevant information available.
- Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

### 5 Fire-fighting measures

- Extinguishing media
- Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam. (Contd. on page 3)

Printing date 03/25/2016 Reviewed on 02/24/2015

Trade name: Dyno

(Contd. of page 2)

- · Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- · Protective equipment: No special measures required.

#### 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### 7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- Specific end use(s) No further relevant information available.

#### 8 Exposure controls/personal protection

- Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

### 111-76-2 2-butoxyethanol

PEL Long-term value: 240 mg/m³, 50 ppm Skin

(Contd. on page 4)

Printing date 03/25/2016 Reviewed on 02/24/2015

Trade name: Dyno

		(Contd. of page 3)
REL	Long-term value: 24 mg/m³, 5 ppm Skin	
TLV	Long-term value: 97 mg/m³, 20 ppm BEI	
1310	7-73-2 sodium hydroxide	
PEL	Long-term value: 2 mg/m³	
REL	Ceiling limit value: 2 mg/m³	
TLV	Ceiling limit value: 2 mg/m³	
· Ingr	edients with biological limit values:	
111-	76-2 2-butoxyethanol	
	200 mg/g creatinine Medium: urine Time: end of shift Parameter: Butoxyacetic acid with hydrolysis	

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Protection of hands:



#### Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

Printing date 03/25/2016 Reviewed on 02/24/2015

Trade name: Dyno

· Eye protection:

(Contd. of page 4)



Tightly sealed goggles

Information on basic physical and	chemical properties
General Information	
Appearance: Form:	In water
Color:	Violet
Odor:	Pleasant
Odor threshold:	Not determined.
pH-value at 20 °C (68 °F):	12.5
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	100 °C (212 °F)
Flash point:	Not applicable.
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	240 °C (464 °F)
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product does not present an explosion hazard.
Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
Vapor pressure at 20 °C (68 °F):	23 hPa (17 mm Hg)
Density at 20 °C (68 °F):	1.03 g/cm³ (8.595 lbs/gal)
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Fully miscible.
Partition coefficient (n-octanol/wat	er): Not determined.
Viscosity:	
Dynamic:	Not determined.

(Contd. on page 6)

### Safety Data Sheet

Printing date 03/25/2016 Reviewed on 02/24/2015

Trade name: Dyno

(Contd. of page 5)

Other information

No further relevant information available.

### 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- \* Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- Incompatible materials: No further relevant information available.
- \*Hazardous decomposition products: No dangerous decomposition products known.

### 11 Toxicological information

- Information on toxicological effects
- Acute toxicity:
- LD/LC50 values that are relevant for classification:
- 1310-73-2 sodium hydroxide

Oral LD50 2000 mg/kg (rat)

- Primary irritant effect:
- on the skin: Caustic effect on skin and mucous membranes.
- on the eye: Strong caustic effect.
- Sensitization: No sensitizing effects known.
- Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Corrosive

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

- · Carcinogenic categories
- · NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

### 12 Ecological information

- · Toxicity
- Aquatic toxicity: No further relevant information available.
- \* Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
- Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.

(Contd. on page 7)

### Safety Data Sheet

Printing date 03/25/2016 Reviewed on 02/24/2015

Trade name: Dyno

#### Additional ecological information:

(Contd. of page 6)

General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Rinse off of bigger amounts into drains or the aquatic environment may lead to increased pH-values. A high pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably reduced, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

- Results of PBT and vPvB assessment
- \*PBT: Not applicable.
- · vPvB: Not applicable.
- Other adverse effects No further relevant information available.

### 13 Disposal considerations

- Waste treatment methods
- Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- \*Uncleaned packagings:
- \*Recommendation: Disposal must be made according to official regulations.
- \*Recommended cleansing agent: Water, if necessary with cleansing agents.

UN-Number	
DOT	NA1760
IMDG, IATA	UN3267
UN proper shipping name	
DOT	Compounds, cleaning liquid (sodium hydroxide) (Sodiur hydroxide)
IMDG	CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S (SODIUM HYDROXIDE)
IATA	Corrosive liquid, basic, organic, n.o.s. (Sodium hydroxide)



Class 8 Corrosive substances

(Contd. on page 8)

Printing date 03/25/2016 Reviewed on 02/24/2015

Trade name: Dyno

	(Contd. of page
Label	8
IMDG, IATA	
£2	
Class	8 Corrosive substances
Label	8
Packing group DOT, IMDG, IATA	III
Environmental hazards: Marine pollutant:	No
Special precautions for user	Warning: Corrosive substances
Danger code (Kemler):	80
EMS Number:	F-A,S-B Alkalis
Segregation groups Stowage Category	Airaiis
Stowage Code	SW2 Clear of living quarters.
Segregation Code	SG35 Stow "separated from" acids.
Transport in bulk according to Annex MARPOL73/78 and the IBC Code	Il of Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 5 L
	On cargo aircraft only: 60 L
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 3267 CORROSIVE LIQUID, BASIC, ORGANI
•	N.O.S. (SODIUM HYDROXIDE), 8, III

### 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sага
- Section 355 (extremely hazardous substances):

None of the ingredients is listed.

- · Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

(Contd. on page 9)

Printing date 03/25/2016

Reviewed on 02/24/2015

Trade name: Dyno

	(Contd. of page
Chemicals known to cause reproductive toxicity for females:	
None of the ingredients is listed.	
Chemicals known to cause reproductive toxicity for males:	
None of the ingredients is listed.	
Chemicals known to cause developmental toxicity:	
None of the ingredients is listed.	
Carcinogenic categories	
EPA (Environmental Protection Agency)	
111-76-2 2-butoxyethanol	N
TLV (Threshold Limit Value established by ACGIH)	
TLV (Threshold Limit Value established by ACGIH) 111-76-2 2-butoxyethanol	A
,	A

The product is classified and labeled according to the Globally Harmonized System (GHS).

GHŠ05

· Signal word Danger

GHS label elements

Hazard pictograms

Hazard statements

Causes severe skin burns and eye damage.

Precautionary statements

Do not breathe dusts or mists.

Wear eye protection / face protection.

Wash thoroughly after handling.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER/doctor.

Specific treatment (see on this label).

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Wash contaminated clothing before reuse.

If eye irritation persists: Get medical advice/attention.

If swallowed: Rinse mouth. Do NOT induce vomiting.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 10)

Printing date 03/25/2016 Reviewed on 02/24/2015

Trade name: Dyno

(Contd. of page 9)

· Department issuing SDS: Environment protection department.

Contact: Enviornmental Department

Date of preparation / last revision 03/25/2016 / -

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Skin Corr. 1A: Skin corrosion/irritation, Hazard Category 1A

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

LIS.