SAFETY DATA SHEET



Mr. Muscle Oven and Grill Cleaner

Version Number: 2 Preparation date: 2015-01-13

1. IDENTIFICATION

Product name:

Mr. Muscle Oven and Grill Cleaner

Product Code:

991206

SDS #:

MS0800125

Recommended use:

• Industrial/Institutional

Oven and Grill Cleaner

Uses advised against:

Uses other than those identified are not recommended

Manufacturer, importer, supplier:

Consumer Branded Professional Products

Diversey, Inc. 8310 16th Street

Sturtevant, Wisconsin 53177-1964

Emergency telephone number:

Phone: (888) 352-2249

Canadian Headquarters Diversey, Inc. - Canada 3755 Laird Road

Mississauga, Ontario L5L 0B3 Phone: 1-800-668-3131

1-800-851-7145 (U.S.); 1-651-917-6133 (Int'l)

2. HAZARDS IDENTIFICATION

Classification for the undiluted product

Skin corrosion/irritation

Serious eye damage/eye irritation

Flammability
Metal Corrosion:

Category 1B Category 1

Extremely flammable aerosol, Category 1

Category 1



Signal Word:

Danger

Precautionary Statements

EXTREMELY FLAMMABLE AEROSOL. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. CAUSES SEVERE SKIN BURNS AND SERIOUS EYE DAMAGE. MAY BE CORROSIVE TO METALS.

Causes burns/ serious damage to mouth, throat and stomach. Avoid contact with eyes, skin and clothing. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Keep container tightly closed. Keep only in original container. Do not pierce or burn, even after use. Do not incinerate. Do not breathe spray. Wash affected areas thoroughly after handling. Wear chemical-splash goggles, long chemical-resistant gloves and protective footwear when spraying and wiping. Do not spray towards face. IF SWALLOWED: Rinse mouth. DO NOT induce vomiting unless directed to do so by medical personnel. Drink a cupful of milk or water. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water for at least 15 minutes. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing for at least 15 minutes. Immediately call a Poison Center (1-800-851-7145) or physician. Wash contaminated clothing before reuse. Absorb spillage to prevent material damage. Store in corrosive-resistant container with a resistant inner liner. Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding 50 °C (122 °F) which may cause bursting. Dispose of in accordance with all federal, state and local applicable regulations.

Mr. Muscle Oven and Grill Cleaner

Diversey



Health hazards not otherwise classified (HHNOC) - Not applicable Physical hazards not otherwise classified (PHNOC) - Not applicable

Classification for the diluted product @ RTU

This product is intended to be used neat.

Precautionary Statements

None required.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Classified Ingredients

Ingredient(s)	CAS#	Weight %
Diethylene glycol butyl ether	112-34-5	10 - 20%
Sodium hydroxide	1310-73-2	3% - < 5%
Butane	106-97-8	1% - < 3%
Isobutane	75-28-5	1% - < 3%
Monoethanolamine	141-43-5	1% - < 3%

^{*}Exact percentages are being withheld as trade secret information

4. FIRST AID MEASURES

<u>Undiluted Product:</u>

Eyes: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing for at least 15 minutes.

Skin: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water for at least 15 minutes.

Inhalation: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Ingestion: IF SWALLOWED: Rinse mouth. DO NOT induce vomiting unless directed to do so by medical personnel. Drink a cupful of milk or water.

Most Important Symptoms/Effects: No information available.

Immediate medical attention and special treatment needed Not applicable.

Aggravated Medical Conditions: Individuals with chronic respiratory disorders such as asthma, chronic bronchitis, emphysema, etc., may be more susceptible to irritating effects.

Diluted Product:

This product is intended to be used neat.

Eyes: Rinse with plenty of water If imitation occurs and persists, get medical attention. Skin: Rinse with plenty of water if imitation occurs and persists, get medical attention, inhalation: No specific first aid measures are required ingestion: Rinse mouth with water.

5. FIRE-FIGHTING MEASURES

Specific methods:

Use water spray to keep fire-exposed containers cool Aerosol Product - Containers may rocket or

explode in heat of fire

Suitable extinguishing media:

Specific hazards:

Dry chemical, water spray, foam.

NFPA 30B Level 1 Aerosol, Aerosol product - Containers may rocket or explode in heat of fire.

Special protective equipment for firefighters: As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Extinguishing media which must not be used for safety reasons: No information available.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: **Environmental precautions** and clean-up methods:

Remove all sources of ignition. Put on appropriate personal protective equipment (see Section 8.). Prevent product from entering drains. Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal. Use a water rinse for final clean-up.

Mr. Muscle Oven and Grill Cleaner

7. HANDLING AND STORAGE

Handling: Avoid contact with skin, eyes and clothing. Avoid breathing vapors or mists. ALWAYS WEAR LONG CHEMICAL-RESISTANT GLOVES, CHEMICAL-SPLASH GOGGLES AND PROTECTIVE FOOTWEAR WHEN SPRAYING AND WIPING. Do not spray toward face. Wash hands and arms after use. Do not spray on or let spray contact pilot light, electrical connections, switches, light bulbs, heating elements, receptacles, or thermostats. Spray may cause electric short. Do not let product contact floor coverings, linoleum, aluminum, copper, chrome, painted surfaces or plastics. Do not use on continuous or self-cleaning ovens. FOR COMMERCIAL AND INDUSTRIAL USE ONLY.

Protect from freezing. Keep out of the reach of children. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 degrees C or 120 degrees F. Exposure to heat may cause bursting. Do not pierce or burn, even after use. Store in a cool, dry, well ventilated area away from heat or open flame.

Aerosol Level (if applicable): Level 1

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines:

Ingredient(s)	CAS#	ACGIH	OSHA
Diethylene glycol butyl ether	112-34-5	10 ppm (TWA)	-
Sodium hydroxide	1310-73-2	2 mg/m³ (Ceiling)	2 mg/m³ (TWA)
Isobutane	75-28-5	1000 ppm (STEL)	-
Butane	106-97-8	1000 ppm (STEL)	-
Monoethanolamine	141-43-5	6 ppm (STEL) 3 ppm (TWA)	3 ppm (TWA) 6 mg/m³ (TWA)

Undiluted Product:

Engineering measures to reduce exposure:

Good general ventilation should be sufficient to control airborne levels Respiratory protection is not required if good ventilation is maintained.

Personal Protective Equipment

Eye protection:

Chemical-splash goggles.

Hand protection:

Skin and body protection: Respiratory protection:

Long chemical-resistant gloves. Protective footwear. If major exposure is possible, wear suitable protective clothing and footwear.

In case of insufficient ventilation wear suitable respiratory equipment. A respiratory protection program

that meets OSHA's 29 CFR 1910,134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

Hygiene measures:

Handle in accordance with good industrial hygiene and safety practice.

Diluted Product:

This product is intended to be used neat.

Personal Protective Equipment

Eye protection:

Hand protection: Skin and body protection:

Respiratory protection:

Chemical-splash goggles:

Long chemical-resistant gloves.

Profective footwear: If major exposure is possible, wear suitable protective clothing and footwear. In case of insufficient ventilation wear suitable respiratory equipment. A respiratory protection program

Boiling point/range: Not determined

Solubility: Completely Soluble

Decomposition temperature: Not determined

Relative Density (relative to water): 1.049

Vapor density: No information available

Vapor pressure: No information available.

that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements must be followed whenever

workplace conditions warrant a respirator's use

Hygiene measures: Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES:

Color: Tan Odor: Citrus

Physical State: Aerosol

Evaporation Rate: No information available Odor threshold: No information available.

Melting point/range: Not determined Autoignition temperature: No information available Solubility in other solvents: No information available

Density: 8.75 lbs/gal 1.049 Kg/L Bulk density: No information available

19 °F Flash point: Dilution Flash Point: 19 °F .-7 °C

pH: 13

Elemental Phosphorus: 0 % by wt.

Partition coefficient (n-octanol/water): No information available Viscosity: No information available VOC: 7.9 %

VOC % by wt. at use dilution 7.9 % * Dilution pH: 13 @ RTU Flammability (Solid or Gas): Not applicable

Metal Corrosion: Not determined

Explosion limits: - upper: Not determined - lower: Not determined

* - Title 17, California Code of Regulations, Division 3, Chapter 1, Subchapter 8.5, Article 2, Consumer Products, Sections 94508

10. STABILITY AND REACTIVITY

Reactivity: Not Applicable Stability: The product is stable

Hazardous decomposition products: No

None reasonably foreseeable.

Materials to avoid:

Strong oxidising agents. Strong acids.

Conditions to avoid: Keep away from open flames, hot surfaces and sources of ignition.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure:

Skin contact, Inhalation, Eye contact, Ingestion

Delayed, immediate, or chronic effects and symptoms from short and long-term exposure

Skin contact: Corrosive. Causes severe burns. Symptoms may include burns, blisters, redness and pain (which may be delayed). **Eye contact:** Corrosive. Causes serious eye damage. Symptoms may include pain, burning sensation, redness, watering, blurred vision or loss of vision.

Ingestion: Causes burns/ serious damage to mouth, throat and stomach. Symptoms may include stomach pain and nausea. **Inhalation:** May cause irritation and corrosive effects to nose, throat and respiratory tract. Symptoms may include coughing and difficulty breathing.

Sensitization: No known effects.

Numerical measures of toxicity

 ATE - Orai (mg/kg):
 >5000 mg/kg

 ATE - Dermal (mg/kg):
 >5000 mg/kg

 ATE - Inhalatory, mists (mg/l):
 >20 mg/L

 ATE - Inhalatory, vapors (mg/l):
 >50 mg/L

12. ECOLOGICAL INFORMATION

Ecotoxicity: No information available.

Persistence and Degradability: No information available.

Bioaccumulation: No information available.

13. DISPOSAL CONSIDERATIONS

Waste from residues / unused products: This product, as sold, if discarded or disposed, is a hazardous waste according to Federal regulations (40 CFR 261.4 (b)(4)). Dispose in compliance with all Federal, state, provincial, and local laws and regulations.

Contaminated Packaging: Do not re-use empty containers.

RCRA Hazard Class (undiluted product): D001 Ignitable Waste, D002 Corrosive Waste

14. TRANSPORT INFORMATION

<u>DOT/TDG/IMDG:</u> Please refer to the Diversey HazMat Library, only available through Internet Explorer, http://naextranet.diversey.com/dot/, for up to date shipping information.

DOT (Ground) Bill of Lading Description: LTD. QTY.

IMDG (Ocean) Bill of Lading Description: UN1950, AEROSOLS, 2.1, LTD. QTY.

15. REGULATORY INFORMATION

International Inventories at CAS# Level

All components of this product are listed on the following inventories: U.S.A. (TSCA), Canada (DSL/NDSL).

U.S. Regulations

California Proposition 65: This product is not subject to the reporting requirements under California's Proposition 65.

RIGHT TO KNOW (RTK)

Ingredient(s)	CAS#	MARTK:	NJRTK:	PARTK:	RIRTK:
Water	7732-18-5	-	-	-	-
Diethylene glycol butyl ether	112-34-5		Х	-	-
Sodium hydroxide	1310-73-2	X	Х	Х	Х
Butane	106-97-8	Х	Х	Х	-
Isobutane	75-28-5	Х	Х	Х	-
Monoethanolamine	141-43-5	Х	Х	Х	-

CERCLA/ SARA

ingredient(s)	CAS#	Weight %	CERCLA/SARA RQ (Ibs)	Section 302 TPQ (ibs)	Section 313
Diethylene glycol butyl ether	112-34-5	10 - 20%			Х
Sodium hydroxide	1310-73-2	3% - < 5%	1000		

Ingredient(s)	CAA HAP	CAA ODS	CWA Priority Pollutants
Diethylene glycol butyl ether	X		

SARA 311/312 Hazard Categories

Immediate: X
Delayed: Fire: X
Reactivity: Sudden Release of Pressure: X

Ingredient(s)	CAS#	NPRI
Diethylene glycol butyl ether	112-34-5	X

16, OTHER INFORMATION

NFPA (National Fire Protection Association)

Rating Scale: (Low Hazard) 0 - 4 (Extreme Hazard)

Health 3 Flammability 4 Instability 0

Version Number: 2

Preparation date: 2015-01-13

Reason for revision: Prepared by: Additional advice: Not applicable NAPRAC

NFPA 30B Level 1 Aerosol

· Contains an added fragrance, see "Odor" heading in section 9 for specific description

Notice to Reader: This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained within. Actual conditions of use and handling are beyond seller's control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State, Provincial and Local laws and regulations.