

## Safet Si

Spartan Chemical Company, Inc.

Revision Date: 22-Jul-2015

Product Identifier

**Product Name:** 

BLOC-AID

**Product Number:** 

7380 , 7585

Recommended Use:

Drain treatment

**Uses Advised Against:** 

For Industrial and Institutional Use Only

Manufacturer/Supplier:

Spartan Chemical Company, Inc.

1110 Spartan Drive

Maumee, Ohio 43537 USA 800-537-89\$0 (Business hours) www.spartahchemical.com

24 Hour Emergency Phone Numbers:

Medical Emergency/Information:

888-314-6171

Transportation/Spill/Leak:

CHEMTRE \$ 800-424-9300

**GHS Classification** 

Skin Corrosion/Irritation:

Category 1

Serious Eye Damage/Eye Irritation:

Category 1

Sub-category A

Corrosive to Metals:

Category 1

**GHS Label Elements** 

Signal Word:

Symbols:

Danger



Hazard Statements:

Causes severe skin burns and serious eye damage.

May be composive to metals.

Precautionary Statements:

Prevention:

Do not breathe mist, vapors or spray.

Wash hands and any exposed skin thoroughly after handling.

Wear protective gloves. Wear eye / face protection. Wear protective clothing.

Keep in original or other corrosion resistant container.

Response:

-Eyes

IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

-Skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water

or shower. Wash contaminated clothing before reuse.

-Inhalation:

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing.

-Ingestion:

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

-Specific Treatment:

See Safety Data Sheet Section 4: "FIRST AID MEASURES" for additional information.

Spill:

Absorb spillage to prevent material damage.

Storage:

Store locked up. Store in corrosion resistant container.

7380 - BLOC-AID

Revision Date: 22-Jul-2015

Disposal:

Dispose of dontents and container in accordance with local, state and federal regulations.

Hazards Not Otherwise Classified:

ed: Not Applicable

Other Information:

· Corrosive.

May be fatal if swallowed.

Harmful contact may not cause immediate pain.

Inhalation of vapors or mist may cause respiratory irritation or damage.

Take off and destroy contaminated shoes.

· Keep out of reach of children.

• NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric

lavage.

Chemical Name	CAS No	Weight-%
water	7732-18-5	40-70
sodium hydroxide	1310-73-2	15-40

Specific chemical identity and/or exact percentage of composition has been withheld as a trade secret.

HARTHER BOND LANGUE TO SAME

-Eye Contact:

Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN. Take off immediately all contaminated clothing and shoes. Rinse with water or shower for

-Skin Contact:

at least 15 minutes. IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN. Wash contaminated clothing before reuse. Discard or destroy contaminated shoes.

-Inhalation:

Remove victim to fresh air and keep at rest in a position comfortable for breathing.

IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN.

-Ingestion:

Rinse mouth. Do NOT induce vomiting. IMMEDIATELY CALL A POISON CENTER OR

PHYSICIAN. Never give anything by mouth to an unconscious person.

Note to Physicians:

NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric

lavage.

Suitable Extinguishing Media:

Product does not support combustion, Use extinguishing agent suitable for type of

surrounding fire

Specific Hazards Arising from the

Chemical:

Dried product is capable of burning. Combustion products are toxic.

**Hazardous Combustion Products:** 

May include Carbon monoxide Carbon dioxide and other toxic gases or vapors.

Protective Equipment and Precautions for Firefighters: Wear MSHA/NIOSH approved self-contained breathing apparatus (SCBA) and full

protective dear. Cool fire-exposed containers with water spray.

Personal Precautions: Environmental Precautions: Methods for Clean-Up: Avoid contact with skin, eyes or clothing. Use personal protective equipment as required.

Do not rinse spill onto the ground, into storm sewers or bodies of water.

Prevent further leakage or spillage if safe to do so. Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see Section 13).

7380 - BLOC-AID Revision Date: 22-Jul-2015

Advice on Safe Handling:

Handle in adcordance with good industrial hygiene and safety practice. Wash thoroughly

after handling.

Storage Conditions:

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep out of the reach

of children. Keep from freezing.

Incompatible Materials:

Reactive metals such as aluminum, zinc and tin. Contact with metals may evolve flammable

hydrogen gas.

Occupational Exposure Limits:

Chemical Name	A¢GIH TLV	OSHA PEL	NIOSH
sodium hydroxide	Ceiling: 2 mg/m <sup>3</sup>	TWA: 2 mg/m³	IDLH: 10 mg/m³
1310-73-2	<u> </u>	(vacated) Ceiling: 2 mg/m³	Ceiling: 2 mg/m³

**Engineering Controls:** 

Provide good general ventilation.

If work practices generate dust, fumes, gas, vapors or mists which expose workers to chemicals above the occupational exposure limits, local exhaust ventilation or other

engineering controls should be considered.

Eye wash stations and shower facilities should be readily accessible in areas where the

product is handled.

Personal Protective Equipment

Eye/Face Protection:

Skin and Body Protection:

Wear splash goggles. For severe use-conditions, wear a face shield over the goggles.

Wear rubber or other chemical-resistant gloves. Use of impervious apron, boots and other protective equipment should be considered in order to prevent or minimize contact with this

product.

**Respiratory Protection:** 

Not required with expected use.

If occupational exposure limits are exceeded or respiratory irritation occurs, use of a

NIOSH/MSHA approved respirator suitable for the use-conditions and chemicals in Section

3 should be considered.

**General Hygiene Considerations:** 

Wash hands and any exposed skin thoroughly after handling. See 29 CFR 1910.132-138 for further guidance.

Sealed T. F. Control	REMANDLE REDUCAMENO RESULTANTA DE LA MESTA DE LA REMANDA DEL REMANDA DE LA REMANDA DEL REMANDA DE LA REMANDA DE LA REMANDA DE LA REMANDA DEL REMANDA DE LA REMANDA DE LA REMANDA DE LA REMANDA DEL REMANDA DE LA REMANDA DEL REMANDA DE LA REMANDA DE LA REMANDA DE LA REMANDA DE LA REMAN		
Appearance/Physical State:	Liquid		
Color:	Red		
Odor:	Odorless		
pH:	> 13.5		
Melting Point / Freezing Point:	No information available.		
Boiling Point / Boiling Range:	124 °C / 255 °F		
Flash Point:	> 124 °C / > 255 °F ASTM D56		
Evaporation Rate:	< 1 (BuAc = 1)		
Flammability (solid, gas)	No information available.		
Upper Flammability Limit:	No information available.		
Lower Flammability Limit:	No information available.		
Vapor Pressure:	No information available.		
Vapor Density:	No information available.		
Specific Gravity:	1.38		
Solubility(ies):	Soluble in water		
Partition Coefficient:	No information available.		
Autoignition Temperature:	No information available.		
Decomposition Temperature:	No information available.		
Viscosity:	No information available.		

Reactivity:

This material is considered to be non-reactive under normal conditions of use.

Chemical Stability:

Stable under normal conditions.

Possibility of Hazardous Reactions: Contact with aluminum or other reactive metals may release hydrogen gas. Heat is

generated when mixed with water.

**Conditions to Avoid:** 

Extremes of temperature and direct sunlight

7380 - BLOC-AID

Revision Date: 22-Jul-2015

Incompatible Materials:

Reactive metals such as aluminum, zinc and tin. Contact with metals may evolve flammable

hydrogen gas.

**Hazardous Decomposition** 

Products:

May include carbon monoxide, carbon dioxide (CO2) and other toxic gases or vapors.

Likely Routes of Exposure: Symptoms of Exposure:

Eyes, Skin, Ingestion, Inhalation.

-Eye Contact:

Pain, redness, swelling of the conjunctiva and tissue damage. Eye contact may cause

permanent damage.

-Skin Contact:

Pain, redness, blistering and possible chemical burn.

-Inhalation:

Irritation or damage to the mucus membranes of the respiratory tract. Nasal discomfort and

-Ingestion:

Damage or chemical burns to mouth, throat and stomach. Pain, nausea, vomiting and

diarrhea.

Immediate, Delayed, Chronic Effects

Product Information:

Data not available or insufficient for classification.

**Target Organ Effects:** 

-Eyes. Respiratory System. -Skin.

**Numerical Measures of Toxicity** 

The following acute toxicity estimates (ATE) are calculated based on the GHS document.

ATEmix (dermal):

3858 mg/kg

Component Acute Toxicity Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
water 7732-18-5	> 90 mL/kg (Rat)	Not Available	Not Available
sodium hydroxide 1310-73-2	Not Available	= 1350 mg/kg ( Rabbit )	Not Available

Carcinogenicity: No components present at 0.1% or greater are listed as to being carcinogens by ACGIH, IARC, NTP or OSHA.

Ecotoxicity	
	And The State of The State of Manager And

Chemical Name	Algae/Aquatic Plants	Fish	Toxicity to Microorganisms	Crustacea
sodium hydroxide 1310-73-2	Not Available	45.4: 96 h Oncorhynchus mykiss mg/L LC50 static	Not Available	Not Available

Persistence and Degradability:

No information available.

Bioaccumulation:

No information available.

Other Adverse Effects:

No information available.

**Disposal of Wastes:** 

Dispose of ih accordance with federal, state and local regulations. Dispose of in accordance with federal, state and local regulations.

**Contaminated Packaging: US EPA Waste Number:** 

D002

DOT:

UN/ID No:

UN1760

**Proper Shipping Name:** 

Corrosive liquid, n.o.s., (contains sodium hydroxide)

**Hazard Class:** 

Packing Group:

II

Revision Date: 22-Jul-2015

Reportable Quantity (RQ):

For totes add: RQ, I.B.C.

Special Provisions:

Shipping descriptions may vary based on mode of transport, quantities, package size, and/or origin and destination. Check with a trained hazardous materials transportation

expert for information specific to your situation.

IMDG:

UN/ID No:

UN1760

**Proper Shipping Name:** 

Corrosive liquid, n.o.s., (contains sodium hydroxide)

**Hazard Class:** 

Packing Group:

Reportable Quantity (RQ):

For totes add: RQ, I.B.C.

TSCA Status: (Toxic Substance Control Act Section 8(b) Inventory)

All chemical substances in this product are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

**SARA 313** 

This product does not contain listed substances above the "de minimus" level

SARA 311/312 Hazard Categories

Acute Health Hazard:

Yes

Chronic Health Hazard:

No

Fire Hazard:

No

Sudden release of pressure hazard:

No

Reactive Hazard:

Yes

California Proposition 65

This product is not subject to warning requirements under California Proposition 65.

NFPA HMIS Health Hazards: 4

Flammability: 0

Instability: 1

Special: N/A

Health Hazards: 4

Flammability: 0

Physical Hazards: 1

**Revision Date:** 

22-Jul-2015

Reasons for Revision:

Section 14 and 15

Disclaimer:

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**