

NITRILE DIPPED

Nitrile Abrasion



Tear

Puncture

GL615

Nylon + Spandex | Nitrile | Micro-Foam



ANSI/ISEA 105 – CUT A1 | ABRASION 6 | PUNCTURE 2 EN388 – ABRASION 4 | CUT 1 | TEAR 3 | PUNCTURE 1 | CUT TDM-100 X

Micro-foam nitrile coating on palm and fingers offers an excellent grip on dry or wet surfaces by channeling liquids away // 15 gauge nylon/spandex liner is comfortable and breathable // Glove design offers distinctive touch sensitivity // Knit cuff creates a snug fit to keep out debris // Dark liner and coating hide stains // Hangtag option for retail display

Suggested Applications

Automotive // Construction // General Duty/Purpose // Horticulture // Manufacturing // Warehousing

Glove Breakdown

Type: Dipped Glove
Material: Micro-Foam Nitrile
Outer Liner: 15 Gauge Nylon + Spandex
Cuff: Nylon + Latex Elastic

▲ WARNING: Cancer and Reproductive Harm –P65Warnings.ca.gov This product contains components that may be a potential risk to allergic reactions (latex in the wrist cuff). Do not use in the event of hypersensitivity signs or a known allergy to latex.

Packaging

		Outer Polybag	Case			
	GL615	12 Pair	120 Pair			
	GL615HT	12 Pair on Hangtags	120 Pair			
	Made in China					

Product markings may vary // Updated as of 04.23



Glove Sizing

Small	Medium	Large	X-Large	2X-Large
7	8	9	10	11

All sizes comply with EN ISO 21420 for comfort, fit and dexterity. Only wear the correct size for your hand. Gloves that are too loose or too tight will restrict movement and will not provide the optimal level of protection.



PYRAMEX[®] *** *** - • • • • * * P 800.736.8673 // F 901.861.4967 // W PYRAMEX.COM